Information processing device

Publication number:	CN1383070 (A)	**Also published as:**
Publication date:	2002-12-04	CN1181436 (C)
Inventor(s):	HIROYUKI UDONO [JP]; TAKAHIRO SATO [JP]; SEI USUI [JP]	US2002157085 (A1)
Applicant(s):	MATSUSHITA ELECTRIC IND CO LTD [JP]	
Classification:		
- international:	**G06F9/44; G06F11/22; G06F12/14; G06F21/00; G06F9/44; G06F11/22; G06F12/14; G06F21/00;** (IPC1-7): G06F12/14; G06F11/22	
- European:	G06F21/00N1V3	
Application number:	CN20021018082 20020422	
Priority number(s):	JP20010122435 20010420	

Abstract not available for CN 1383070 (A)
Abstract of corresponding document: **US 2002157085 (A1)**

An information processing apparatus configured so as to be connectable to a debugging terminal includes: a CPU for executing a program; a monitor section for monitoring an execution status of the program, a debug communication section configured so as to be connectable to the debugging terminal; and an authentification section connected to the monitor section and the debug communication section, wherein the debug communication section receives debug information from the debugging terminal, the authentification section determines whether or not the monitor section is allowed to output monitor information corresponding to the debug information, according to whether the authentification section is in an authentificated state or in an unauthentificated state, and the debug communication section transmits to the debugging terminal the monitor information output from the monitor section.